

**REQUEST FOR PROPOSAL
NAVAJO POLICE DEPARTMENT
UNIFORM PURCHASE**

BID NUMBER. 18-10-1949VJ

I. PURPOSE OF REQUEST.

The purpose of this invitation to bid is to purchase uniforms for use by the Navajo Police Department (NPD). The basis of award will involve several considerations, to include uniform quality, fit, design, service, and price considering estimated quantities of uniforms and apparel to be purchased by the NPD. The successful vendor shall meet all Special Conditions and Garment Specifications as outlined herein. The successful bidder will furnish uniforms as ordered in consultation with the successful vendor.

II. TIME SCHEDULE.

It is the NPD's intent to follow this process and timetable, resulting in the selection of a vendor. At the NPD's discretion, it may change the estimated dates and the process set forth below as it deems necessary including but not limited to interviews.

NPD issues RFP.	November 28, 2018
Deadline for Submittal of Proposals by 12:00 PM.	January 2, 2019
Evaluation of submitted proposals	January 2, 2019
Notice of conditional selection and initiate award process	January 9, 2019
Award by the Navajo Nation (tentative date)	April 10, 2019

III. INSTRUCTION FOR PROPOSERS.

A. All proposals* must be addressed to:

Delivery: Victor Joe, Buyer
Purchasing Service Department
Admin Building One
Window Rock Boulevard
Window Rock, Arizona 86515

Mailing: Victor Joe, Buyer
Purchasing Service Department
Post Office Box 9000
Window Rock, Arizona 86515

*Note this delivery and address surname is limited only to the proposal delivery and mailing.

- B. Any questions or inquiries regarding the scope of purchase should be brought to the attention of

Leonard Redhorse III, Police Lieutenant
Office of the Chief of Police
Navajo Police Department
928-871-6363
lredhorse@navajo-nsn.gov

- C. All proposals must be in a sealed envelope and clearly marked "**NPD UNIFORM PURCHASE. 18-10-1949VJ**". The name and address of the proposing vendor must be shown on the face of the envelope.
- D. All proposals must be received by 12:00pm on Wednesday, January 2, 2019. Proposals will not be accepted after this deadline. Two (2) copies of the proposal must be enclosed in the sealed envelope. No facsimile, electronic or telephone proposals will be accepted.
- E. Proposals should be prepared simply and economically, providing a straight forward, concise description of provider capabilities to satisfy the requirements of the request. Special bindings, colored displays, promotional materials, etc. are not desired. Emphasis should be on completeness and clarity of content.
- F. The NPD will notify proposers of the outcome of their proposals on or near the date indicated in the above time schedule.
- G. Proposal Submittal must include:
1. Company name and address, as well as the name and direct contact information of the primary and secondary account representatives. Briefly describe the primary and secondary account representatives' experience delivering services to Police organizations similar in size and scope of those listed under the Scope of Services in this RFP and years of service at your company.
 2. What is the Lead Time to deliver product After Receipt of Order? Define the process and timeline you anticipate for delivery of the identified goods.
 3. A statement that your firm/company is available to measure Police personnel in the seven police districts of NPD for accurate measurements.
 4. Describe your relationship with the Manufacturer of the uniforms and apparel proposed for this RFP. Include how you plan to

guarantee continuity of supply, quality and uniformity of appearance throughout the life of the resulting purchase.

5. What is the estimated lifespan of each proposed garment given normal wearing conditions?
6. List three (3) references whom the NPD can contact, from agencies of similar size that have purchased police uniforms from your company within the last two (3) years. Include the name and address of each referenced organization, as well as the name, title, and phone number of the contact person. The NPD reserves the option to check references at its sole discretion.
7. At the NPD's option, top ranked firms/companies may be requested to supply sample garments for review prior to contract award.
8. Identify from what location the proposer will provide the identified goods to the NPD.
9. Describe systems and mechanisms that would be established for status reporting during the project.
10. Proposer shall acknowledge the purchase will be made using a Navajo Nation Purchase Order.
11. A completed W-9 Form (Exhibit B)
12. A Navajo Nation Certification Regarding Debarment and Suspension (Exhibit C)
13. A statement identifying your firm/company has Reviewed the Purchase Order Terms and Conditions (Exhibit D) [Note, the Terms and Conditions are binding and take precedence.] and there is a understanding of that review.
14. A statement identifying your firm/company has Reviewed the Uniform Specification for the Navajo Police Department (Exhibit E) and the proposal meets the required specifications.

IV. **SELECTION CRITERIA.**

The NPD will use the following criteria in its evaluation and comparison of proposals submitted. The order in which they appear is not intended to indicate their relative importance.

WEIGHTING FACTOR	QUALIFICATION	STANDARDS
2	Scope of Proposal	Does the proposal address all elements of the RFP? Does the proposal show an understanding of the project objectives, methodology to be used and results/outcomes required by the project? Are there any exceptions to the Scope of Services, Specifications or Terms?
2	Assigned Personnel	Do the account representatives have the necessary skills and years of experience delivering service of similar scope? Are sufficient people of the requisite skills and qualifications assigned to the project?
1	Availability	Can the target Lead Time be met? Are other qualified personnel available to assist Police personnel when needed? Is the vendor available to measure Police personnel as required by the Scope of Services?
1	Sustainability	What is the estimated lifespan of each proposed garment given normal wearing conditions
2	Cost	Does the proposal include detailed cost break-down for each cost element as applicable and are the line item costs competitive? Do the proposed costs compare favorably with the NPD's estimate?
2	Firm Capability	Does the firm have the resources, capacity and support capabilities required to successfully deliver quality service and product?
1	References	Does the firm have positive references that corollate to successful project completion?
1	Acknowledgements	Did the firm/company acknowledge that a purchase order will be used? Did the firm/company provide their current W-9 and debarment? Did the firm/company state they reviewed the terms and conditions? Did the firm/company state they reviewed the specifications and that their proposal meets the required specifications?

The NPD shall not be obligated to accept the lowest priced proposal, but shall make an award to the most responsible and responsive proposer whose proposal is most advantageous to and best serves the needs of the NPD and the Navajo Nation taking into consideration price and the evaluation factors set forth.

V. SCOPE OF PURCHASE.

The scope of purchase to be covered are attached herein as Exhibit A.

VI. TERMS AND CONDITIONS.

A. The NPD reserves the right to reject any and all proposals, and to waive

minor irregularities in any proposal.

- B. The NPD reserves the right to request clarification of information submitted, and to request additional information from any proposer.
- C. The information submitted will be analyzed and may be shared internally, appear in reports, as appropriate and at the NPD's discretion. Proprietary, classified, confidential, or sensitive information should be clearly marked in your response. The NPD reserves the right to use any non-proprietary information. No basis for claims against the NPD shall arise as a result of a response to this RFP or from the NPD's use of such information.
- D. The NPD reserves the right to award all or a portion of the required goods to more than one qualified proposer at the NPD's sole discretion.
- E. The purchase order resulting from acceptance of a proposal by the NPD shall be in a form supplied or approved by the NPD and shall reflect the specifications in this RFP. The Purchase Order Terms and Conditions is attached.
- F. After preliminary selection and prior to contract award, the NPD will meet with the Proposer to review procedures for invoicing, payment, reporting, if any, and monitoring contract performance.
- G. The NPD shall not be responsible for any costs incurred by the Proposer in preparing, submitting or presenting its response to this RFP.
- H. The successful proposer agrees to reimburse the Navajo Police Department the cost for advertising this RFP.
- I. Nothing in the RFP is intended to or shall have the effect of waiving any privileges or immunities afforded the Navajo Nation including, but not limited to, sovereign immunity or official immunity and it is expressly agreed that the Navajo Nation retains such privileges.
- J. The Navajo Nation is a sovereign government and all contracts entered into as a result of the RFP shall comply with the Navajo Nation law, rules and regulations, including the Navajo Preference in Employment Act, and applicable federal law, rules and regulations.

VII. **COMPENSATION**

- A. Present detailed information for the identified goods, inclusive of Navajo Nation sales tax (6%) [24 NNC § 201 et seq.]. The Navajo Nation will not pay any other tax associated to this goods purchase.
- B. In the event you have specific questions regarding the applicability of this

tax, please contact the Office of the Navajo Tax Commission, Compliance Department at 928-871-6681.

- C. Payment by the NPD for the identified goods will only be made after the identified goods have been delivered and accepted by authorized NPD representatives. The NPD requires that all its vendors have a Department of Treasury Internal Revenue Service Form W-9 on file with the NPD to accommodate payment. Itemized billings shall be submitted upon completion containing information specified by the NPD as described in Exhibit A.

VIII. **LICENSE REQUIREMENT**

- A. The Navajo Nation requires the successful proposer, at its sole expense, to procure and maintain adequate and sufficient insurance for all potential liability, such as commercial general liability, automobile liability, worker's compensation, professional liability errors and omissions liability, etc.

EXHIBIT A

SCOPE OF PURCHASE

The Navajo Police Department is requesting proposals on the following for purchase using a Navajo Nation Purchase Order. Please review the *Purchase Order Terms and Conditions* and the *Uniform Specifications for the Navajo Police Department Specifications* which are attached. Please include the shipping as a separate line item.

The successful vendor will measure / fit employees at no additional cost to obtain a proper fit for each employee. Measurements will be performed within twenty (20) calendar days of request. This process will determine the sizes needed for the respective item.

I. ANNUAL OFFICER ORDER

- a. Description: Police 6 Pocket Uniform Trouser
 - 1. 75% Polyester 25% Wool 12oz Serge Top Dyed w/ NanoTex
 - 2. Taupe
- ii. Quantity: 1200

- b. Description: Uniform Shirt – Short Sleeve
 - 1. 75% Polyester/ 25% Wool 9 1/2 oz. Tropical Weave Stock Dyed
 - 2. Taupe
- ii. Quantity: 600

- c. Description: Uniform Shirt – Long Sleeve
 - 1. 75% Polyester/ 25% Wool 9 1/2 oz. Tropical Weave Stock Dyed
 - 2. Taupe
- ii. Quantity: 600

II. Drop Shipment

- a. Navajo Police Department HQ, Property Warehouse #1, Navajo Route 12, Building 2639, Fort Defiance, Arizona 86504

- b. This is NOT the billing address. Only the shipping address. Billing is the address below.

Please include the time frame for delivery of each line item.

The Billing address will be:

Attn: Financial Management
Office of the Chief of Police
Navajo Police Department
Post Office Box 3360
Window Rock, Arizona 86515
928-871-6363

EXHIBIT B

FORM W-9 (Rev. 11-2017)

Request for Taxpayer Identification Number and Certification

**Give Form to the
 requester. Do not
 send to the IRS.**

▶ Go to www.irs.gov/FormW9 for instructions and the latest information.

Print or type. See Specific Instructions on page 3.	<p>1 Name (as shown on your income tax return). Name is required on this line; do not leave this line blank.</p> <hr/> <p>2 Business name/disregarded entity name, if different from above</p> <hr/> <p>3 Check appropriate box for federal tax classification of the person whose name is entered on line 1. Check only one of the following seven boxes.</p> <p><input type="checkbox"/> Individual/sole proprietor or single-member LLC <input type="checkbox"/> C Corporation <input type="checkbox"/> S Corporation <input type="checkbox"/> Partnership <input type="checkbox"/> Trust/estate</p> <p><input type="checkbox"/> Limited liability company. Enter the tax classification (C=C corporation, S=S corporation, P=Partnership) ▶ _____</p> <p>Note: Check the appropriate box in the line above for the tax classification of the single-member owner. Do not check LLC if the LLC is classified as a single-member LLC that is disregarded from the owner unless the owner of the LLC is another LLC that is not disregarded from the owner for U.S. federal tax purposes. Otherwise, a single-member LLC that is disregarded from the owner should check the appropriate box for the tax classification of its owner.</p> <p><input type="checkbox"/> Other (see instructions) ▶ _____</p>	<p>4 Exemptions (codes apply only to certain entities, not individuals; see instructions on page 3):</p> <p>Exempt payee code (if any) _____</p> <p>Exemption from FATCA reporting code (if any) _____</p> <p><small>(Applies to accounts maintained outside the U.S.)</small></p>
	<p>5 Address (number, street, and apt. or suite no.) See instructions.</p> <hr/> <p>6 City, state, and ZIP code</p> <hr/> <p>7 List account number(s) here (optional)</p>	<p>Requester's name and address (optional)</p> <hr/>

Part I Taxpayer Identification Number (TIN)

Enter your TIN in the appropriate box. The TIN provided must match the name given on line 1 to avoid backup withholding. For individuals, this is generally your social security number (SSN). However, for a resident alien, sole proprietor, or disregarded entity, see the instructions for Part I, later. For other entities, it is your employer identification number (EIN). If you do not have a number, see *How to get a TIN*, later.

Note: If the account is in more than one name, see the instructions for line 1. Also see *What Name and Number To Give the Requester* for guidelines on whose number to enter.

Social security number											
				-			-				
or											
Employer identification number											
				-							

Part II Certification

Under penalties of perjury, I certify that:

1. The number shown on this form is my correct taxpayer identification number (or I am waiting for a number to be issued to me); and
2. I am not subject to backup withholding because: (a) I am exempt from backup withholding, or (b) I have not been notified by the Internal Revenue Service (IRS) that I am subject to backup withholding as a result of a failure to report all interest or dividends, or (c) the IRS has notified me that I am no longer subject to backup withholding; and
3. I am a U.S. citizen or other U.S. person (defined below); and
4. The FATCA code(s) entered on this form (if any) indicating that I am exempt from FATCA reporting is correct.

Certification instructions. You must cross out item 2 above if you have been notified by the IRS that you are currently subject to backup withholding because you have failed to report all interest and dividends on your tax return. For real estate transactions, item 2 does not apply. For mortgage interest paid, acquisition or abandonment of secured property, cancellation of debt, contributions to an individual retirement arrangement (IRA), and generally, payments other than interest and dividends, you are not required to sign the certification, but you must provide your correct TIN. See the instructions for Part II, later.

Sign Here	Signature of U.S. person ▶	Date ▶
------------------	----------------------------	--------

General Instructions

Section references are to the Internal Revenue Code unless otherwise noted.

Future developments. For the latest information about developments related to Form W-9 and its instructions, such as legislation enacted after they were published, go to www.irs.gov/FormW9.

Purpose of Form

An individual or entity (Form W-9 requester) who is required to file an information return with the IRS must obtain your correct taxpayer identification number (TIN) which may be your social security number (SSN), individual taxpayer identification number (ITIN), adoption taxpayer identification number (ATIN), or employer identification number (EIN), to report on an information return the amount paid to you, or other amount reportable on an information return. Examples of information returns include, but are not limited to, the following.

- Form 1099-DIV (dividends or distributions)

- Form 1099-DIV (dividends, including those from stocks or mutual funds)
- Form 1099-MISC (various types of income, prizes, awards, or gross proceeds)
- Form 1099-B (stock or mutual fund sales and certain other transactions by brokers)
- Form 1099-S (proceeds from real estate transactions)
- Form 1099-K (merchant card and third party network transactions)
- Form 1098 (home mortgage interest), 1098-E (student loan interest), 1098-T (tuition)
- Form 1099-C (canceled debt)
- Form 1099-A (acquisition or abandonment of secured property)

Use Form W-9 only if you are a U.S. person (including a resident alien), to provide your correct TIN.

If you do not return Form W-9 to the requester with a TIN, you might be subject to backup withholding. See What is backup withholding, later.

Exhibit C

NAVAJO NATION CERTIFICATION Regarding Debarment and Suspension

Applicant acknowledges that to the best of his/her knowledge that their company and principal participants on this contract:

1. Are not debarred, suspended, or otherwise slated for debarment, ineligible and/or excluded from participation on Federal, State, and Tribal Government contracts etc.
2. Are not presently nor have been under criminal indictment or civilly charged by a governmental entity (Federal, State, and Tribal Government) for fraud, forgery, falsification, theft, bribery, destruction of records, receiving stolen property and other criminal offenses in the administration of a government contract.
3. Have not been terminated for cause or convenience by a governmental entity in the administration of a government contract (Federal, State, and Tribal Government).
4. If the Navajo Nation determines that the Certificate provided herein is not true, it will be grounds to terminate the contract and pursue other legal remedies.

Applicant's Address

Name & Signature of Applicant

Type or Print Name

Signature Date

EXHIBIT E

UNIFORM SPECIFICATIONS FOR THE NAVAJO POLICE DEPARTMENT

SPECIAL CONDITIONS

PURPOSE: The purpose of this invitation to bid is to purchase various items of uniform apparel for use by the Navajo Police Department (NPD).

The basis of award will involve several considerations, to include uniform quality, fit, design, service, and price considering estimated quantities of uniforms and apparel to be purchased by the NPD. The successful vendor shall meet all Special Conditions and Garment Specifications as outlined herein. The successful bidder will furnish uniforms as ordered in consultation with the successful vendor.

BIDDERS INQUIRIES: The bidder shall examine the solicitation to determine if the requirements are clearly stated. Questions concerning conditions and specifications of this solicitation should be directed to the point of contact established under III.B of the bid announcement.

MEASUREMENTS: The successful bidder shall ensure a proper fit for all employees. Upon request by the Department, the successful bidder shall measure/fit employees at no additional cost to the Department, to obtain a proper fit for any employee experiencing problems with measuring and proper fit of the uniform items. Measurements will be performed within twenty (20) calendar days of request. Bidder shall provide on-site measuring for all recruit classes.

DELIVERY: An order is considered complete when all patches, stripes and emblems are installed. All orders shall be shipped with the Officer's name attached to each uniform package or if there are multiple uniform orders that are shipped at the same time, each uniform order shall be included in its own packaging and labeled with the Officer's name.

LABELING: All garments must have a care label permanently affixed giving the care instructions and must show the lot number, size, fiber content and WPL number of the garment. The labels for permanent press or fine washables shall reflect specific washing care instructions.

EMBLEMS, LOGO'S, EMBELISHMENTS: All prices are to include the necessary emblems, and embellishments. ***Emblems will be furnished to the successful bidder. The cost to sew them on is the sole responsibility of the vendor. Shirts and Jackets are to include the Agency Emblem on each sleeve.***

WARRANTY: All material shall be new, of current manufacture and shall carry the standard warranties prescribed for each specified fabric. Vendor shall submit to the Department, if requested, new fabrics to test as they come on the market. Additional or reduced cost for new fabrics for each item shall be negotiated and agreed upon in writing. Supporting documentation showing increased or decreased costs shall include invoices of old fabric vs. cost of new fabric.

Workmanship and products shall be in accordance with standard practices of the trade. Special attention is directed to the fact that seams tearing at the seam line, gathering of fabric or puckering of garments after wear or use is not acceptable. Garments must be fully warranted against defects for a minimum of 90 days.

PRICES: Bid must be submitted in a manner that answers the "*Exhibit A Scope of Purchase.*". A price of each item must be listed or the bid will be rejected. Prices shall be F.O.B., Window Rock, AZ. The Navajo Nation will only pay the Navajo Nation Sales Tax of 6% [24 NNC § 201 et seq.]. The Navajo

Nation will not pay any other tax associated to this goods purchase. Please refer to VII.A-C of this bid announcement.

Industry-wide price reductions shall be accorded to the Navajo Police Department during the period of this purchase.

AWARD: This bid will be awarded to a single vendor based on the total aggregate price bid for those items indicated on the Bid Form as well as the vendor's ability to meet the other required criteria (within a maximum of 30 working days after opening. A tentative award by the NPD should occur by February 4, 2019. The Navajo Police Department reserves the right to make split or multiple awards based on this single solicitation.

CUSTOMER SERVICE REPRESENTATIVE: As part of the bid, the successful bidder shall provide the name, address and telephone number of at least two customer service representatives assigned to the purchase. These persons shall be available to meet prior to the purchase and on a quarterly basis, if requested, and to service the account, taking measurements, etc. All costs associated with the customer service representative shall be the responsibility of the successful bidder.

REFERENCES: Each bidder shall list the names of at least three customers that the bidder is currently supplying, with service requirements similar to those sought herein, i.e. stocking uniform supplier, on-site customer measurement. Unverifiable or unsatisfactory references; or references for services not comparable to those sought herein, may lead to rejection of a bid as non-responsive to this requirement. Vendor's ability to meet requirements under previous contracts may be considered.

SPECIFICATIONS: All specifications have been provide, herein, to establish the required minimum quality standard.

ADDITIONS / DELETIONS: Items discontinued by the Navajo Police Department will be deleted from any order awarded in accordance with this invitation to bid. Items may be deleted for other appropriate reasons as well. Additional or replacement garments and/ or related items may be added by mutual consent, with specifications and prices agreed upon by the parties. Fabric, material, design, or construction changes to garments and/or related items may be requested, with specifications and prices agreed upon by the parties.

MALE POLICE 6 POCKET UNIFORM TROUSER

Description: MALE POLICE 6 POCKET UNIFORM TROUSER

Sizes: 28 – 46 Standard, 48 and up Special

Color: Taupe

Fabric: 75% Polyester 25% Wool 12oz Serge Top Dyed w/ NanoTex

Style: The pant shall have a plain front with quarter top front pockets, 1" wide belt loops, two back pockets for a clean professional appearance. The pant cuff shall be of open construction to allow for custom finishing and shall have a 37 ½" inch inseam (unfinished).

Pockets: The front pocket opening shall be a minimum 6½" long and be 6" deep from the bottom of the pocket opening. The inside front pocket facing shall be a separate piece of self-material finishing no less than 1" wide. There shall be a hidden vault pocket in the right hand front pocket secured with a #3 YKK invisible zipper. The back pockets will have a minimum opening of 5½" and be 7 1/2" deep. Each back pocket shall have a 1 1/4" loop closure tab with a bar tack located 3/8" from point of attachment to secure the buttonhole. The loop tab shall attach to a ligne 20, durable button. Each pocket corner shall have a 3/8" triangle bar tack for reinforcement.

There shall be two cut in cargo pockets centered on each outside side seam with the top opening positioned 3" below the side pockets. Pocket shall be a minimum of 7" wide (the width increases with graded sizes) X 9 ½" deep. There shall be a center tab on the outside seam attached by two bar tacks to secure a reinforced ligne 14, durable button centered along the bottom edge of the pocket bag. The pocket shall be closed with a #3 YKK nylon coil zipper with a 1" pocket welt. **(Hidden & Secure (H&S cargo™) cargo pocket.**

Buttons: All buttons shall be 100% Polyester and shall pass ASTM 5171-1191.84 kg mass dropped from a height of 67mm. The buttons shall be pearlized.

Pocketing: All pocketing shall be heavy-duty black 150-denier 70% Polyester/30% Cotton tuxedo pocketing with a minimum thread count of 82 x 64. The waistband and inside seam binding shall be made with pocketing material cut on the bias.

Waistband: The waistband shall be designed to allow for 4" of mechanical expansion through two unique double waistband panels with 1¼" elastic built in. **(Expand on Demand® waistband)** The front waistband shall be held with a hidden 6" X 1 1/4" elastic attached to a tapered tab of self-material. The inside waistband shall be held with 7" X 1 ¼" elastic sewn to the waistband inside fold back to a separate enclosed channel which is joined to the front waistband channel at the top of the front pocket opening. The elastic shall remain concealed even when the waistband is stretched to its maximum length. The curtain, shall be made of the heavy duty tuxedo pocketing material listed above, bias-cut, and shall have a continuous parallel 7/16" wide silicone band designed to work with the corresponding SPDU shirt for maximum shirt retention **(SRS® Shirt Retention System)**. The finished waistband shall be 2 1/8" wide and shall be closed with two crush-proof riveted oxidized metal hook and eyes. The finished waistband shall be set on and shall be stitched below the lower edge through the outer fabric and the waistband curtain.

Inner Fly/Crotch:

The right fly and front crotch linings shall be the same fabric and color as the waistband curtain. There shall be a TC #8000 interlining sewn between the fly and the fly lining to give additional stability and strength to the fly. The right fly lining shall be sewn to the left fly below the zipper and continue centered on the join seam across the inseam and end 1" onto the back seam. A separate French fly made of the outer fabric with a lining of

reinforced pocketing shall be sewn to the inside right fly. The fly attachment button shall be a ligne 20, 100% polyester durable button. The button shall pass ASTM 5171-1191, using a .84 kg mass dropped from 67 mm.

There shall be a diamond shaped reinforced crotch gusset measuring 9" wide X 4 ¾" sewn with a five needle safety stitch to prevent crotch seam failure.

Zipper: The trousers shall be closed with a #4 YKK brass memory lock zipper and have a brass bottom stop at the base of the zipper chain. A straight bar tack shall be sewn through from the outside of the garment to the inside at the bottom of the fly. The bar tack shall be sewn through the zipper tape; the right and left fly and the right fly lining. The right and left fly shall be joined by an additional bar tack located at level of the bottom zipper stop on the inside of the trouser.

Belt Loops: There should be a minimum of 5 lined belt loops on waist sizes 28, 29, 30, and a minimum of 7 lined loops on all sizes over 30. Each loop is to be 1" wide of double thickness, with stitching on the face side ⅜" from each edge. Except for the center back loop, which shall be tacked on, all loops shall be sewn into the bottom of the waistband and into the rocap.

Creasing: The front and back crease in the trouser legs shall incorporate a permanent resin bonded silicone crease produced by the Creaset™ System. The crease shall be properly cured to insure that the crease is permanent so that no amount of home laundering shall remove the crease.

Stripe: There shall be a 1" Spruce Green Stripe sewn from the waistband down the side of each outseam and MUST WRAP POCKET WELT. Stripe shall be free from puckering and shall be made using a corresponding fabric.

Seaming: The entire trouser is to be seamed with Polyester core or 100% Polyester spun thread. If necessary, use steam iron, low setting.

Labels: The trouser shall have a sewn-in label giving care instructions and an outside waistband label which shall be marked with lot number, size, fiber content, and cut number. A permanent size label shall be sewn inside on the hip pocket.

Care Instructions:

Dry Clean or Machine wash in warm water in gentle cycle. Wash dark colors separately and rinse thoroughly. Do not bleach. Tumble-dry completely at low heat and remove promptly. If necessary, use steam iron, low setting.

Sizes: Men's waist sizes as listed below.

28 30 31 32 33 34 35 36 37 38 40 42 44 46 48 50 52 54 56 58 60 62 64 66

ADDITIONAL REQUIREMENTS: Failure to provide any of the following will be cause for rejection.

- **Manufacturer must be ISO 9001: 2015 certified and a copy of certificate shall be included with bid and dated prior to bid release date.**
- **Manufacturer must provide a published lifetime or limited lifetime warranty against product defects and component failure. There will be no special/alternate warranties accepted for this item.**

- **A representative size run of this item as specified must be provided with vendors bid. This size run will include sizes 30, 32, 34, 36, 38, 40, 42, 44 and will be kept with the Department for the duration of this purchase.**

FEMALE POLICE 6 POCKET UNIFORM PANT

Description: FEMALE POLICE 6 POCKET UNIFORM PANT
Sizes: 4-24 Standard, 26 and up Special
Color: *Taupe*
Fabric: 75% Polyester 25% Wool 12oz Serge Top Dyed w/ NanoTex

STYLE: The pant shall have a plain front with quarter top front pockets, 1" wide belt loops, two back pockets for a clean and professional appearance. The pant cuff shall be of open construction to allow for custom finishing and shall have a 35-inch inseam (unfinished). Female pattern shall be current to Departments standards.

POCKETS: The front pocket opening shall be a minimum 6½" long and be 6" deep from the bottom of the pocket opening. The inside front pocket facing shall be a separate piece of self-material finishing no less than 1" wide. There shall be a hidden vault pocket in the right hand front pocket secured with a #3 YKK invisible zipper. The back pockets will have a minimum opening of 5½" and be 7 1/2" deep. Each back pocket shall have a 1 1/4" loop closure tab with a bar tack located 3/8" from point of attachment to secure the buttonhole. The loop tab shall attach to a ligne 20, durable button. Each pocket corner shall have a 3/8" triangle bar tack for reinforcement.

There shall be two cut in cargo pockets centered on each outside side seam with the top opening positioned 3" below the side pockets. Pocket shall be a minimum of 7" wide (the width increases with graded sizes) X 9 ½" deep. There shall be a center tab on the outside seam attached by two bar tacks to secure a reinforced ligne 14, durable button centered along the bottom edge of the pocket bag. The pocket shall be closed with a #3 YKK nylon coil zipper with a 1" pocket welt. **(Hidden & Secure (H&S cargo™) cargo pocket.**

BUTTONS: All buttons shall be 100% Polyester and shall pass ASTM 5171-1191.84 kg mass dropped from a height of 67mm. The buttons shall be pearlized.

POCKETING: All pocketing shall be heavy-duty black 150 denier 70% polyester / 30% cotton tuxedo pocketing with a minimum thread count of 82 x 64. The waistband and inside seam binding shall be made with pocketing material cut on the bias.

WAISTBAND: The waistband shall be designed to allow for approximately 4" of mechanical expansion through two unique double waistband panels with built in elastic 1 ¼" wide. (Expand On Demand Waistband®). The outer front waistband shall be held with hidden 6" x 1 ¼" elastic attached to a tapered tab of self material. The inside waistband shall be held with 7" x 1 ¼" elastic sewn inside and folded back into a separate enclosed channel joined to the front waistband channel at the top of the front pocket opening. The elastic shall remain concealed even when the waistband is stretched to maximum potential. The curtain shall be made of heavy duty tuxedo pocketing material, bias-cut, and shall have a continuous parallel of 7/16" rectangular piece of silicone designed to work with the corresponding SPDU shirts for shirt retention (SRS® Shirt Retention System). The finished waistband shall be 2 1/8" wide and shall be closed with two crush-proof riveted oxidized metal hook and eyes. The finished waistband shall be set on and shall be stitched below the lower edge through the outer fabric and the waistband curtain.

INNER FLY/CROTCH:

The right fly and front crotch linings shall be the same fabric and color as the waistband curtain. There shall be a TC #8000 interlining sewn between the fly and the fly lining to give additional stability and strength to the fly. The right fly lining shall be sewn to the left fly below the zipper and continue centered on the join seam across the inseam and end 1" onto the back seam. A separate French fly made of the outer fabric with a lining of

reinforced pocketing shall be sewn to the inside right fly. The fly attachment button shall be a ligne 20, 100% polyester durable button. The button shall pass ASTM 5171-1191, using a .84 kg mass dropped from 67 mm.

ZIPPER: The trousers shall close with a #4 YKK brass memory lock zipper and have a brass bottom stop at the base of the zipper chain. A straight bar tack shall be sewn through from the outside of the garment to the inside at the bottom of the fly. The bar tack shall be sewn through the zipper tape; the right and left fly and the right fly lining. The right and left fly shall be joined by an additional bar tack located at level of the bottom zipper stop on the inside of the trouser.

BELT LOOPS: Each loop is to be 1" wide of double thickness, with stitching on the face side $\frac{3}{8}$ " from each edge. Except for the center back loop, which shall be tacked on, all loops shall be sewn into the bottom of the waistband and into the rocap.

CREASING: The front and back crease in the trouser legs shall incorporate permanent resin bonded silicone crease produced by Creaset™. The crease shall be properly cured to insure that it remains permanent and no amount of home laundering shall remove the crease.

STRIPE: There shall be a 1" Spruce Green Stripe sewn from the waistband down the side of each outseam and MUST WRAP POCKET WELT. Stripe shall be free from puckering and shall be made using a corresponding fabric.

SEAMING: The entire trouser is to be seamed with Polyester core or 100% Polyester spun thread.

LABELS: The trouser shall have a sewn-in label giving care instructions and an outside waistband label which shall be marked with lot number, size, fiber content, and cut number. A permanent size label shall be sewn inside on the hip pocket.

CARE INSTRUCTIONS:

Dry Clean or Machine wash in warm water in gentle cycle. Wash dark colors separately and rinse thoroughly. Do not bleach. Tumble-dry completely at low heat and remove promptly. If necessary, use steam iron, low setting.

Sizes: Female sizes as listed below.

4 6 8 10 12 14 16 18 20 22 24 26 28

ADDITIONAL REQUIREMENTS: Failure to provide any of the following will be cause for rejection.

- **Manufacturer must be ISO 9001: 2015 certified and a copy of certificate shall be included with bid and dated prior to bid release date.**
- **Manufacturer must provide a published lifetime or limited lifetime warranty against product defects and component failure. There will be no special/alternate warranties accepted for this item.**
- **A representative size run of this item as specified must be provided with vendors bid.**

UNIFORM SHIRT-MALE SHORT SLEEVE

- Description:** UNIFORM SHIRT – MALE SHORT SLEEVE
- Sizes:** 14.5-18.5 Standard, 19 and up Special
- Color:** Taupe
- Fabric:** 75% Polyester/ 25% Wool 9 1/2 oz. Tropical Weave Stock Dyed
- Style:** The Shirt shall be standard military style with shirttails and permanently stitched two (2) front and three (3) back creases.
- Tailoring:** This garment shall be constructed according to the principles set forth in the specifications. All stitches shall be of the proper tension and size so as to avoid puckering after the shirt has been laundered and to give best durable press performance. All sewing shall be with polyester core thread to match shirt fabric. The collar and cuffs are to be single stitched 1/4" from edge. The pockets, flaps and epaulets shall be edge stitched.
- Collar:** The collar points shall be medium spread approximately 3" in length. The outside edge of the collar shall be stitched with a 1/4" edge stitch. The collar width at the back of the neck shall be 1 3/4". The inside collar stand shall have a sateen fabric lining for comfort. There shall be a collar stay sewn inside the collar along the bottom edge of each collar to hold the collar shape and still allow the attachment of collar brass. The collar shall be designed to wear with the collar points spread.
- Sleeves:** The sleeves shall be one piece sewn into the shoulder, and finished with a 1" clean turn-up with no loose threads. The sleeves and side closing seams shall be attached to the body of the shirt with an overlock and a safety stitch for reinforcement.
- Epaulets:** The epaulets shall be sewn onto the shoulder seam and shall extend to within 1/2" of the collar seam. The epaulet shall button at point 1" from the collar seam. The epaulet shall be 2 1/8" wide at the shoulder seam and taper to 1 5/8", then to a point. The overall length of the epaulet shall be approximately 8". The epaulet shall be double thickness with a single edge stitch on the perimeter. The epaulets shall be box stitched to shoulders with row of cross-stitching 2 1/2" from sleeve head seam. There shall be a hidden ligne 16 button attached 1 3/8" from the epaulet attachment button on each side under each epaulet to attach a unique microphone sling (patent applied for) to insure that the radio microphone is in the proper place to be deployed. Epaulets shall be contrasting Black in Color
- Front:** The front shall have a center facing 1-1/2" wide placket extending from the collar to the bottom of shirt. The placket shall have an interlining for stability and a neat appearance and shall be 1/4" top stitched on each side. The center front placket shall contain vertical buttonholes placed 3/4" from edge and 3-1/2" apart. There shall be a button at the neck corresponding with the top buttonhole, which shall be set horizontally. There shall be a spare ligne 20 button sewn into the inside button facing. There shall be a hidden zipper sewn under the front placket of the shirt. There shall be 4 rectangular bands of silicone approximately 3 1/8" x 9/16" sewn 2" above the bottom of exterior shirt tail edge on front and back. The silicone bars are designed to work with the corresponding SPDU pant waistband for maximum shirt retention (SRS® shirt retention system).
- Mic Tab:** Each shirt will include a removeable mic clip that can be attached along the placket of the shirt or positioned at either side of shirt with a hidden button beneath each shoulder epaulet. This tab is to be made from and match shirt fabric.

Camera Tab: Self fabric tab to be sewn on front shirt placket per department specifications. This tab is designed to securely hold body worn camera.

Back: The garment shall have a straight yoke back located approximately 4 ¼" below the collar seam. The inside yoke shall be lined with 100% Polyester Taffeta.

Pockets: The shirt shall have two Military-styled box pleated, breast patch pockets with 3-point button down flaps. The breast pocket shall be 5 5/8" wide X 6 3/8" long. The center bellows pleat shall be 1 ½" wide. The bottom corners of the pocket shall be cut on a 40 degree angle and shall be 1 ¼" long. The pocket flaps shall be slightly tapered and shall be 6" wide at the top and 6 ¼" wide at the outside points on the bottom of the flap.

The flaps shall be attached to the shirt body 1/4" above the top of the pocket, resulting in a complete pocket measurement of 6 3/8" long. The pocket shall be edge stitched around the perimeter and shall finish with a 3/8" turn down. The pocket corners shall be reinforced with a triangle stitch in each corner. There shall be a pencil opening on both the left and right flap. The two outside points of each pocket flap shall have concealed Velcro™ closures. The left breast pocket shall have a sewn pencil compartment approximately 1-5/8" wide. Each flap shall have a ligne 20 buttons sewn to a false buttonhole on the surface of the flap. (Pocket dimensions shall be graded by shirt size/dimension).

Hidden Chest Pocket:

There shall be a #3 YKK 6 ½" concealed zipper under the front placket on right side of shirt. The pocket height shall be 9" with the pocket width extending from the facing seam to the side seam. The center of the zippered opening shall be centered at the mid- point between the top of the chest flap and the bottom of the chest pocket. The top of the concealed pocket shall align with the top of the pocket flap. Concealed shirt pocket shall be made of shirting material.

Badge Tab: The badge eyelets shall be reinforced on the inside of the shirt by means of a strip of self material measuring 1" wide, edge stitched and folded so that no raw edges appear. The reinforcement strip is to extend from the flap setting stitch to the joining seam at the front of the yoke. There shall be two small (horizontal) sewn eyelets 1-1/4" apart sewn through the left front and the reinforcement strip with the bottom buttonhole located 1-1/4" above the top of left flap. This shall conform to the NPD shield badge sizing and will be verified by the vendor.

Front: The shirt shall also have two permanent 1/16" wide military creases permanently sewn down each side from shoulder seam to bottom of the shirt and centered through each front pocket and pocket flap.

Button: All buttons shall be 100% Polyester and shall pass ASTM 5171-1191.84 kg mass dropped from a height of 67mm. The buttons shall be pearlized.

Emblems: Each shirt shall have a Navajo Police Department emblem attached to each sleeve sewn on at no additional charge. Emblems shall be furnished by the Agency.

Care Instructions:

Dry Clean or Machine wash in warm water in gentle cycle. Wash dark colors separately and rinse thoroughly. Do not bleach. Tumble-dry completely at low heat and remove promptly. If necessary, use steam iron, low setting.

Shirt sizes: Men's Numeric Sizes (14.5,15,15.5,16,16.5,17,17.5,18,18.5,19-19.5,20-20.5,21-21.5)

ADDITIONAL REQUIREMENTS: Failure to provide any of the following will be cause for rejection.

NPD Uniform Purchase
18-10-1949VJ

- **Manufacturer must be ISO 9001: 2015 certified and a copy of certificate shall be included with bid and dated prior to bid release date.**
- **Manufacturer must provide a published lifetime or limited lifetime warranty against product defects and component failure. There will be no special/alternate warranties accepted for this item.**
- **A representative size run of this item as specified must be provided with vendors bid.**

UNIFORM SHIRT-MALE LONG SLEEVE

- Description:** UNIFORMS SHIRT – MALE LONG SLEEVE
- Sizes:** See Size Chart Below
- Color:** Taupe
- Fabric:** 75% Polyester/ 25% Wool 9 1/2 oz. Tropical Weave Stock Dyed
- Style:** The Shirt shall be standard military style with shirttails and permanently stitched two (2) front and three (3) back creases.
- Tailoring:** This garment shall be constructed according to the principles set forth in the specifications. All stitches shall be of the proper tension and size so as to avoid puckering after the shirt has been laundered and to give best durable press performance. All sewing shall be with polyester core thread to match shirt fabric. The collar and cuffs are to be single stitched 1/4" from edge. The pockets, flaps and epaulets shall be edge stitched.
- Collar:** The collar points shall be medium spread approximately 3" in length. The outside edge of the collar shall be stitched with a 1/4" edge stitch. The collar width at the back of the neck shall be 1 3/4". The back of the stand shall measure 1-1/2". The inside collar shall be made of a sateen fabric for comfort. There shall be a collar stay sewn inside the collar along the bottom edge of each collar to hold the collar shape and still allow the attachment of collar brass. There shall be hidden triangle collar button-down tabs sewn underneath each collar point approximately 1" wide (at the attachment point) and 7/8" long. These tabs shall attach to hidden durable ligne 14 buttons which to keep the collar secure.
- Sleeves:** The sleeves shall be one piece sewn into the shoulder, tapering into the finished cuffs with pressed double pleats. The cuffs shall be attached to the sleeve with a 3/8" double needle stitch and shall be 2-5/8" in width; fastening with two durable ligne 20 4 hole 100% polyester buttons. The cuffs shall be made of two pieces of base shirt material with an interlining. There shall be a shirt cuff opening with a facing of shirt material 7" X 1" tapering to a point with a closure stitch across the facing 1 1/2" from the point. There shall be a buttonhole approximately 4" from the point to attach a ligne 16 durable 100% polyester button. The button shall be attached to the inside facing which shall be bound with 5/8" bias cut shirt material for reinforcement. The sleeves and side closing seams shall be attached to the body of the shirt with a merrow and a safety stitch for reinforcement.
- Epaulets:** The epaulets shall be sewn onto the shoulder seam and shall extend to within 1/2" of the collar seam. The epaulet shall button at point 1" from the collar seam. The Epaulet shall be 2 1/8" wide at the shoulder seam and taper to 1 5/8", then to a point. The overall length of the epaulet shall be approximately 8". The epaulet shall be double thickness with a single edge stitch on the perimeter. The epaulets shall be box stitched to shoulders with row of cross-stitching 2 1/2" from sleeve head seam. There shall be a hidden ligne 16 button attached 1 3/8" from the epaulet attachment button on each side under each epaulet to attach a unique microphone sling (patent applied for) to insure that the radio microphone is in the proper place to be deployed. Epaulets to be contrasting Black in Color
- Front:** The front shall have a center facing 1-1/2" wide placket extending from the collar stand to the bottom of shirt. The placket shall have an interlining for stability and a neat appearance and shall be 1/4" top stitched on each side. The center front shall contain six (6) vertical buttonholes placed 3/4" from edge and 3-1/2" apart. There shall be a button at the neck corresponding with the top buttonhole, which shall be set horizontally. There shall be a hidden zipper sewn under the center front placket. There shall be an inside

facing of self-material on the button side 3 1/4" wide extending from the collar stand to bottom of shirt. The buttons shall be securely attached shall correspond to the buttonholes on the center facing. There shall be a spare line 20 and line 16 button sewn into the inside button facing. There shall be 4 bands of silicone 3 1/8" X 9/16" sewn into the bottom of the shirt 2" from the bottom and 1/4" on the inside of the outer creases designed to work with the corresponding SPDU pant waistband for maximum shirt retention (**SRS™ shirt retention system**)

Mic Tab: Each shirt will include a removeable mic clip that can be attached along the placket of the shirt or positioned at either side of shirt with a hidden button beneath each shoulder epaulet. This tab is to be made from and match shirt fabric.

Camera Tab: Self fabric tab to be sewn on front shirt placket per department specifications. This tab is designed to securely hold body worn camera.

Back: The garment shall have a straight yoke back located approximately 4 1/4" below the collar seam. The inside yoke shall be lined with 100% Polyester Taffeta.

Pockets: The shirt shall have two Military-styled box pleated, breast patch pockets with 3-point button down flaps. The breast pocket shall be 5 5/8" wide X 6 3/8" long. The center pleat shall be 1 1/2" wide. The bottom corners of the pocket shall be cut on a 40 degree angle and shall be 1 1/4" long. The pocket flaps shall be slightly tapered and shall be 6" wide at the top and 6 1/4" wide at the outside points on the bottom of the flap. (Pocket dimensions will vary with size) The flaps shall be attached to the shirt body 1/4" above the top of the pocket, resulting in a complete pocket measurement of 6 3/8" long. The pocket shall be edge stitched around the perimeter and shall finish with a 3/8" turn down. The pocket corners shall be reinforced with a triangle stitch in each corner. There shall be a pencil opening on both the left and right flap. The two outside points of each pocket flap shall have concealed Velcro closures. The left breast pocket shall have a sewn pencil compartment approximately 1-5/8" wide. Each flap shall have a line 20 buttons sewn to a false buttonhole on the surface of the flap.

Hidden Chest Pocket:

There shall be a #3 YKK 6 1/2" concealed zipper under the front placket on right side of shirt. The pocket height shall be 9" with the pocket width extending from the facing seam to the side seam. The center of the zippered opening shall be centered at the mid- point between the top of the chest flap and the bottom of the chest pocket. The top of the concealed pocket shall align with the top of the pocket flap. Concealed shirt pocket shall be made of shirting material.

Badge Tab: The badge tab is to be reinforced on inside of the shirt by means of a strip of material 1" wide edge stitched and folded so that no raw edges show. The reinforcement strip is to extend from the flap setting stitch to the joining seam at the front of the yoke. There shall be two small (horizontal) buttonholes, 1-1/4" apart sewn through the left front and the reinforcement strip with the bottom buttonhole located 1-1/4" above the top of left flap. This shall conform to the NPD shield badge sizing and will be verified by the vendor.

Creasing: Pockets and pocket flaps shall be uniform in shape and size. The front and back creases shall incorporate a permanent 1/16" stitched crease.

Back: The shirt shall have 3 permanent creases, 1/16" wide on the back panel. One crease shall be located at the center back and shall start at the center of the yoke and continue straight down to the bottom edge of the shirt. Each of the other two creases shall be located at the midway point between the center crease and the shoulder seam on both the left and right sides of the center crease.

Front: The shirt shall also have two permanent stitched 1/16" wide military creases down each side from the shoulder seam to the bottom of the shirt centered through each front pocket and pocket flap.

Button: All buttons shall be 100% Polyester and shall pass ASTM 5171-1191.84 kg mass dropped from a height of 67mm. The buttons shall be pearlized.

Emblems: Each shirt shall have a Navajo Police Department emblem attached to each sleeve sewn on at no additional charge. Emblems shall be furnished by the Agency.

Care Instructions:
 Dry Clean or Machine wash in warm water in gentle cycle. Wash dark colors separately and rinse thoroughly. Do not bleach. Tumble-dry completely at low heat and remove promptly. If necessary, use steam iron, low setting.

MEN'S L/S SIZE CHART

<u>SPDU75 MEN'S L/S</u>	<u>14 1/2</u>	<u>15</u>	<u>15 1/2</u>	<u>16</u>	<u>16 1/2</u>	<u>17</u>	<u>17 1/2</u>	<u>18</u>	<u>18 1/2</u>	<u>19</u>	<u>20</u>
<i>Sleeve length from CB</i>	30/31	30/31	30/31	-	-	-	-	-	-	-	-
	32/33	32/33	32/33	32/33	32/33	32/33	32/33	32/33	32/33	-	-
	34/35	34/35	34/35	34/35	34/35	34/35	34/35	34/35	34/35	34/35	34/35
	-	-	-	36/37	36/37	36/37	36/37	36/37	36/37	36/37	36/37

<u>SPDU15 MEN'S L/S</u>	<u>21</u>	<u>22</u>
<i>Sleeve length from CB</i>	-	-
	-	-
	34/35	34/35
	36/37	36/37

ADDITIONAL REQUIREMENTS: Failure to provide any of the following will be cause for rejection.

- **Manufacturer must be ISO 9001: 2015 certified and a copy of certificate shall be included with bid and dated prior to bid release date.**
- **Manufacturer must provide a published lifetime or limited lifetime warranty against product defects and component failure. There will be no special/alternate warranties accepted for this item.**
- **A representative size run of this item as specified must be provided with vendors bid.**

UNIFORM SHIRT-FEMALE SHORT SLEEVE

- Description:** UNIFORM SHORT – FEMALE SHORT SLEEVE
- Sizes:** 30-44 Standard, 46 and up Special
- Color:** Taupe
- Fabric:** 75% Polyester/ 25% Wool 9 1/2 oz. Tropical Weave Stock Dyed
- Style:** The Shirt shall be standard military style with shirttails and permanently sewn front and back creases.
- Tailoring:** This garment shall be constructed according to the principles set forth in the specifications. All stitches shall be of the proper tension and size so as to avoid puckering after the shirt has been laundered and to give best durable press performance. All sewing shall be with polyester core thread to match the shirt fabric. The collar shall be single stitched 1/4" from edge. The pockets, flaps and epaulets shall be edge stitched. The shirtsleeve bottom shall be finished with a 1" clean finished.
- Collar:** The collar points shall be medium spread approximately 3" in length. The outside edge of the collar shall be stitched with a 1/4" edge stitch. The Collar width at the back of the neck shall be 1 3/4". The inside collar stand shall be made of a sateen fabric for comfort. There shall be a collar stay sewn inside the collar along the bottom edge of each collar to hold the collar shape and still allow the attachment of collar brass. The collar shall be designed to wear with the collar points spread.
- Sleeves:** The sleeves shall be one piece sewn into the shoulder, and finished with a 1" clean turn-up with no loose threads. The sleeves and side closing seams shall be attached to the body of the shirt with an overlock and a safety stitch for reinforcement.
- Epaulets:** The epaulets shall be sewn onto the shoulder seam and shall extend to within 1/2" of the collar seam. The epaulet shall button at point 1" from the collar seam. The Epaulet shall be 2" wide at the shoulder seam and taper to 1 1/2", then to a point. The overall length of the epaulet shall be approximately 5 5/8". The epaulet shall be double thickness with a single edge stitch on the perimeter. The epaulets shall be box stitched to shoulders with row of cross-stitching 1 5/8" from sleeve head seam. There shall be a hidden button attached 1 3/8" from the epaulet attachment button on each side under each epaulet to attach a unique microphone sling (patent applied for) to insure that the radio microphone is in the proper place to be deployed. Epaulets to be contrasting Black.
- Front:** The front shall have a center facing 1-1/2" wide placket extending from the collar stand to the bottom of shirt. The placket shall have an interlining for stability and a neat appearance and shall be 1/4" top stitched on each side. The center front shall contain six (6) vertical buttonholes placed 3/4" from edge and 3-1/2" apart. There shall be a button at the neck corresponding with the top buttonhole, which shall be set horizontally. There shall be an 18-ligne snap between the third and fourth button from the top to keep the shirt from gapping. There shall be an inside facing of self-material on the button side 3 1/4" wide extending from the collar to bottom of shirt. The buttons shall be securely attached shall correspond to the buttonholes on the center facing. There shall be a spare ligne 20 button sewn into the inside button facing. There shall be a hidden zipper under the front placket of the shirt.
- There shall be 4 bands of silicone 3 1/8" X 9/16" sewn into the bottom of the shirt 2" from the designed to work with the corresponding SPDU pant waistband for maximum shirt retention (**SRS® shirt retention system**)

Mic Tab: Each shirt will include a removeable mic clip that can be attached along the placket of the shirt or positioned at either side of shirt with a hidden button beneath each shoulder epaulet. This tab is to be made from and match shirt fabric.

Camera Tab: Self fabric tab to be sewn on front shirt placket per department specifications. This tab is designed to securely hold body worn camera.

Back: The garment shall have a straight yoke back located approximately 4 ¼" below the collar seam. The inside yoke shall be lined with 100% Polyester Taffeta.

Pockets: The shirt shall have two Military-styled box pleated, breast patch pockets with 3-point button down flaps. The breast pocket shall be 5 ¼" wide X 5 3/8" long. The center pleat shall be 1 ¼" wide. The bottom corners of the pocket shall be cut on a 40 degree angle and shall be 1 ¼" long. The pocket flaps shall be slightly tapered and shall be 5 3/8" wide at the top and 5 ¼" wide at the outside points on the bottom of the flap. (Pocket dimensions will vary with size). The flaps shall be attached to the shirt body 1/4" above the top of the pocket, resulting in a complete pocket measurement of 6" long. The pocket shall be edge stitched around the perimeter and shall finish with a 3/8" turn down. The pocket corners shall be reinforced with a triangle stitch in each corner. There shall be a pencil opening on both the left and right flap. The two outside points of each pocket flap shall have concealed Velcro closures. The left breast pocket shall have a sewn pencil compartment approximately 1-5/8" wide. Each flap shall have a ligne 20 button sewn to a false buttonhole on the surface of the flap.

Hidden Chest Pocket:

There shall be a #3 YKK 6 ½" concealed zipper under the front placket on left side of shirt. The pocket height shall be 9" with the pocket width extending from the facing seam to the side seam. The center of the zippered opening shall be centered at the mid- point between the top of the chest flap and the bottom of the chest pocket. The top of the concealed pocket shall align with the top of the pocket flap. Concealed shirt pocket shall be made of shirting material.

Badge Tab: The badge tab is to be reinforced on inside of the shirt by means of a strip of material 1" wide edge stitched and folded so that no raw edges show. The reinforcement strip is to extend from the flap setting stitch to the joining seam at the front of the yoke. There shall be two small (horizontal) buttonholes, 1-1/4" apart sewn through the left front and the reinforcement strip with the bottom buttonhole located 1-1/4" above the top of left flap. This shall conform to the NPD shield badge sizing and will be verified by the vendor.

Front: The shirt shall also have two permanently sewn 1/16" wide military creases down each side from the shoulder seam to the bottom of the shirt centered through each front pocket and pocket flap.

Button: All buttons shall be 100% Polyester and shall pass ASTM 5171-1191.84 kg mass dropped from a height of 67mm. The buttons shall be pearlized.

Emblems: Each shirt shall have a Navajo Police Department emblem attached to each sleeve sewn on at no additional charge. Emblems shall be furnished by the Agency.

Care Instructions:

Dry Clean or Machine wash in warm water in gentle cycle. Wash dark colors separately and rinse thoroughly. Do not bleach. Tumble-dry completely at low heat and remove promptly. If necessary, use steam iron, low setting.

Shirt sizes: Chest sizes: 30 – 48 (even sizes)

NPD Uniform Purchase
18-10-1949VJ

ADDITIONAL REQUIREMENTS: Failure to provide any of the following will be cause for rejection.

- **Manufacturer must be ISO 9001: 2015 certified and a copy of certificate shall be included with bid and dated prior to bid release date.**
- **Manufacturer must provide a published lifetime or limited lifetime warranty against product defects and component failure. There will be no special/alternate warranties accepted for this item.**
- **A representative size run of this item as specified must be provided with vendors bid**

UNIFORM SHIRT-FEMALE LONG SLEEVE

- Description:** UNIFORM SHIRT – FEMALE LONG SLEEVE
- Sizes:** 30-44 Standard, 46 and up Special
- Color:** Taupe
- Fabric:** 75% Polyester/ 25% Wool 9 1/2 oz. Tropical Weave Stock Dyed
- Style:** The Shirt shall be standard military style with shirrtails and permanent stitched front and back creases.
- Tailoring:** This garment shall be constructed according to the principles set forth in the specifications. All stitches shall be of the proper tension and size so as to avoid puckering after the shirt has been laundered and to give best durable press performance. All sewing shall be with polyester core thread to match shirt fabric. The collar and cuffs are to be single stitched 1/4" from edge. The pockets, flaps and epaulets shall be edge stitched.
- Collar:** The collar points shall be medium spread approximately 3" in length. The outside edge of the collar shall be stitched with a 1/4" edge stitch. The collar width at the back of the neck shall be 1 3/4". The back of the stand shall measure 1-1/2". The inside collar stand shall be made of a sateen fabric for comfort. There shall be a collar stay sewn inside the collar along the bottom edge of each collar to hold the collar shape and still allow the attachment of collar brass. There shall be hidden triangle collar button-down tabs sewn underneath each collar point approximately 1" wide (at the attachment point) and 7/8" long. These tabs shall attach to hidden durable ligne 14 buttons which to keep the collar secure.
- Sleeves:** The sleeves shall be one piece sewn into the shoulder, tapering into the finished cuffs with pressed double pleats. The cuffs shall be attached to the sleeve with a 3/8" double needle stitch and shall be 2-5/8" in width; fastening with two durable ligne 20 4 hole 100% polyester buttons. The cuffs shall be made of two pieces of base shirt material with an interlining. There shall be a shirt cuff opening with a facing of shirt material 7" X 1" tapering to a point with a closure stitch across the facing 1 1/2" from the point. There shall be a buttonhole approximately 4" from the point to attach a ligne 16 durable 100% polyester button. The button shall be attached to the inside facing which shall be bound with 5/8" bias cut shirt material for reinforcement. The sleeves and side closing seams shall be attached to the body of the shirt with a merrow and a safety stitch for reinforcement.
- Epaulets:** The epaulets shall be sewn onto the shoulder seam and shall extend to within 1/2" of the collar seam. The epaulet shall button at point 1" from the collar seam. The Epaulet shall be 2" wide at the shoulder seam and taper to 1 1/2", then to a point. The overall length of the epaulet shall be approximately 5 5/8". The epaulet shall be double thickness with a single edge stitch on the perimeter. . The epaulets shall be box stitched to shoulders with

row of cross-stitching 2 1/2" from sleeve head seam. There shall be a hidden ligne 16 button attached 1 3/8" from the epaulet attachment button on each side under each epaulet to attach a unique microphone sling (patent applied for) to insure that the radio microphone is in the proper place to be deployed.

Front: The front shall have a center facing 1-1/2" wide placket extending from the collar stand to the bottom of shirt. The placket shall have an interlining for stability and a neat appearance and shall be 1/4" top stitched on each side.

The center front shall contain six (6) vertical buttonholes placed 3/4" from edge and 3-1/2" apart. There shall be a button at the neck corresponding with the top buttonhole, which shall be set horizontally. There shall be an 18 ligne snap between the third and fourth button from the top to keep the shirt from gapping. There shall be a hidden zipper under the center front placket of the shirt. There shall be an inside facing of self-material on the button side 3 1/4" wide extending from the collar stand to bottom of shirt. The buttons shall be securely attached shall correspond to the buttonholes on the center facing. There shall be a spare line 20 and line 16 button sewn into the inside button facing. There shall be 4 bands of silicone 3 1/8" X 9/16" sewn into the bottom of the shirt 2" from the bottom and 1/4" on the inside of the outer creases designed to work with the corresponding SPDU pant waistband for maximum shirt retention (**SRS™ shirt retention system**)

Mic Tab: Each shirt will include a removeable mic clip that can be attached along the placket of the shirt or positioned at either side of shirt with a hidden button beneath each shoulder epaulet. This tab is to be made from and match shirt fabric.

Camera Tab: Self fabric tab to be sewn on front shirt placket per department specifications. This tab is designed to securely hold body worn camera.

Back: The garment shall have a straight yoke back located approximately 4 1/4" below the collar seam. The inside yoke shall be lined with 100% Polyester Taffeta.

Pockets: The shirt shall have two Military-styled box pleated, breast patch pockets with 3-point button down flaps. The breast pocket shall be 5 1/4" wide X 5 3/8" long. The center pleat shall be 1 1/8" wide. The bottom corners of the pocket shall be cut on a 40 degree angle and shall be 1 1/4" long. The pocket flaps shall be slightly tapered and shall be 5 3/8" wide at the top and 5 1/4" wide at the outside points on the bottom of the flap. (Pocket dimensions will vary with size) The flaps shall be attached to the shirt body 1/4" above the top of the pocket, resulting in a complete pocket measurement of 6" long. The pocket shall be edge stitched around the perimeter and shall finish with a 3/8" turn down. The pocket corners shall be reinforced with a triangle stitch in each corner. There shall be a pencil opening on both the left and right flap. The two outside points of each pocket flap shall have concealed Velcro closures. The left breast pocket shall have a sewn pencil compartment approximately 1-5/8" wide. Each flap shall have a ligne 20 button sewn to a false buttonhole on the surface of the flap.

Hidden Chest Pocket:

There shall be a #3 YKK 6 1/2" concealed zipper under the front placket on left side of shirt. The pocket height shall be 9" with the pocket width extending from the facing seam to the side seam. The center of the zippered opening shall be centered at the mid- point between the top of the chest flap and the bottom of the chest pocket. The top of the concealed pocket shall align with the top of the pocket flap. Concealed shirt pocket shall be made of shirting material.

Badge Tab: The badge tab is to be reinforced on inside of the shirt by means of a strip of material 1" wide edge stitched and folded so that no raw edges show. The reinforcement strip is to

extend from the flap setting stitch to the joining seam at the front of the yoke. There shall be two small (horizontal) buttonholes, 1-1/4" apart sewn through the left front and the reinforcement strip with the bottom buttonhole located 1-1/4" above the top of left flap. This shall conform to the NPD shield badge sizing and will be verified by the vendor.

Creasing: Pockets and pocket flaps shall be uniform in shape and size. The front and back creases shall incorporate permanent 1/16" stitched creases.
Back: The shirt shall have 3 permanent creases, 1/16" wide on the back panel. One crease shall be located at the center back and shall start at the center of the yoke and continue straight down to the bottom edge of the shirt. Each of the other two creases shall be located at the midway point between the center crease and the shoulder seam on both the left and right sides of the center crease.
Front: The shirt shall also have two permanent stitched 1/16" wide military creases down each side from the shoulder seam to the bottom of the shirt centered through each front pocket and pocket flap.

Button: All buttons shall be 100% Polyester and shall pass ASTM 5171-1191.84 kg mass dropped from a height of 67mm. The buttons shall be pearlized.

Emblems: Each shirt shall have a Navajo Police Department emblem attached to each sleeve sewn on at no additional charge. Emblems shall be furnished by the Agency.

Care Instructions:
Dry Clean or Machine wash in warm water in gentle cycle. Wash dark colors separately and rinse thoroughly. Do not bleach. Tumble-dry completely at low heat and remove promptly. If necessary, use steam iron, low setting.

Shirt sizes: Chest sizes: 30 – 48 (even sizes)

ADDITIONAL REQUIREMENTS: Failure to provide any of the following will be cause for rejection.

- **Manufacturer must be ISO 9001: 2015 certified and a copy of certificate shall be included with bid and dated prior to bid release date.**
- **Manufacturer must provide a published lifetime or limited lifetime warranty against product defects and component failure. There will be no special/alternate warranties accepted for this item.**
- **A representative size run of this item as specified must be provided with vendors bid. This size run will include sizes 14 ½, 15 ½, 16 ½, 17 ½, 18 ½, all in 32/33 sleeve lengths and will be kept with the Department for the duration of this contract.**

SUPPLEMENTAL SPECIFICATION STATEMENT

The Navajo Police Department shall be transitioning from Polyester into Poly-Wool uniform as soon as possible. The Navajo Police Department's new poly-wool uniforms shall be the same taupe color and scheme as our current Navajo Police duty uniform. The taupe colored uniform is unique and is an exclusive representation of the Navajo Police Department.

Poly-Wool Pant: The new poly-wool uniform pant will have upgraded features; e.g.

- Zippered cargo style pockets,
- Reinforced crotch area
- Front and back permanent crease
- 75/25 polyester wool blend fabric
- Silicone Grip Retention System designed to keep shirttails in
- Welt back pockets with button closure
- Deep slash side pockets with hidden security zipper pocket in right pocket
- Welt zippered Hidden & Secure cargo pockets on both thighs
- Heavy-duty tuxedo pocketing
- Triangle bar tacks on pocket stress points
- Heavy-duty riveted hook-and-eye closure system
- Hidden expand-on-demand adjustable waistband
- Comfort gusseted crotch (men's sizes only)
- French fly with bartacks at all stress points
- Brass zipper
- Additional 4 pockets on the poly-wool pant, and green stripe running down the side of the pant.
- The new poly-wool pant will have a total of 8 pockets with the flex-fit waist band.

Poly-Wool Shirt: The new poly-wool shirt will have;

- Full comfort mechanical stretch built into fabric
- Reinforcing separate inside badge sling
- Silicone grip Shirt Retention System, to hold shirt tucked into trouser
- Permanent military stitched creases
- 75-25 Poly-Wool blend
- Zippered front closure
- Hidden chest pocket
- Front edge collar stays
- Hidden double pen pocket on the left chest pocket
- Removable microphone sling
- Body Camera Tab/microphone tab in front of the shirt.
- Poly-wool shirt pockets will have Velcro closure system with the pearlized buttons sewn on the shirt pocket flaps.
- The poly-wool shirt will have two military creases in front and three military creases in the back.
- Badge tab will be reinforced and will have proper Navajo PD Shield Badge sizing

The specifications set forth are to help provide with a description of the minimum requirements.

SPECIFICATION FOR STYLE SH3466
WeatherTech® Systems Airflow Duty Jacket

General Design

The parka shall be a full zip to the neck waterproof/windproof/breathable garment with taped seams, a waterproof, three-piece drop in hood, zipper tracks for optional jacket/liner inserts, and optional Hidden Agenda™ pull down panels for safety and visibility of wearer when needed. All measurements mentioned in the construction specifications are based on stock size Large/Regular.

Shell Fabric:

The shell fabric shall be 3.8oz/yd² 100% Invista™ Tactel® 280D Supplex® Air Texturized Nylon or equal, with a non-ravel polyurethane back coating, and durable water repellent finish. The construction shall be 110 x 54. The shell fabric shall be available in colors Dark Navy, Black, Brown and Police Green.

Shell Fabric Performance Requirements

	Test Method	Requirement
Weight, oz/yd ²	ASTM D3776, Opt C	3.8oz/yd ² (+-5%)
Tensile Strength (Minimum Newtons)	ASTM D5034 C.R.E Grab Method	Warp 550 Fill 950
Tear Strength (minimum Newtons)	ASTM D1424 Pendulum Method	Warp 10 Fill 25
Abrasion Resistance Cycles (minimum). End point when two threads break under 9kPa applied pressure with multidirectional abrasion	ASTM D 4966 Martindale Method	20000 minimum
Seam Slippage (lbf)	ASTM D 434 C.R.E.	Warp: NIL (¼" SO, 67 STB) Fill: NIL (¼' SO, 81 STB)
Spray Rating	AATCC 22	100, 100, 100
Dimensional Stability, (maximum %) after 5 wash cycles	AATCC 135 Test (2)III(A)ii	Warp 3.0 Fill 3.0

The shell fabric shall also meet the following Colorfastness Requirements:

Colorfastness to Gray scale Wet: min 4.5 AATCC 8
Croaking for Staining Dry: min 4.5

Colorfastness to Gray scale Shade Change: min 4.5 AATCC 15

<u>Perspiration</u>	for Staining	Staining of: acetate - min 4.5 cotton - min 4.5 nylon - min 4.5 polyester - min 4.5 acrylic - min 4.5 wool - min 4.5	
<u>Colorfastness to Washing</u>	Gray scale for Staining	Shade Change: min 4.0 Staining of: acetate - min 4.5 cotton - min 4.5 nylon - min 4.0 polyester - min 4.5 acrylic - min 4.5 wool - min 4.5	AATCC 61 2A*

*Modified. 45 min – mechanical wash at 105°F on 0.15% 1993 AATCC standard reference detergent WOB solution with 50 steel balls – 150 ml liquor volume.

<u>Colorfastness to Water</u>	Gray scale for Staining	Shade Change: min 4.5 Staining of: acetate - min 4.5 cotton - min 3.5 nylon - min 3.5 polyester - min 4.5 acrylic - min 4.5 wool - min 4.5	AATCC 107
-------------------------------	-------------------------	---	-----------

Key to AATCC Gray Scale Rating (applies to all above)

- Class 5 – Negligible or no color alteration
- Class 4 – Slight color change
- Class 3 – Noticeable color change
- Class 2 – Considerable color change
- Class 1 – Much color alteration

Lining

The lower inside shell body, full sleeve, hood, and yoke shall be backed by a lining fabric which shall be a WeatherTech® performance fabric of 100% 210T nylon with a waterproof, windproof, and breathable laminate coating. It shall have a Moisture Vapor Transmission Rate of 2000g/m²/24hr Minimum (ASTM E96 procedure BW coating facing water) and Hydrostatic Resistance Rating of 2000mm Minimum (AATCC 127).

All lining joining seams (except attachments to mesh) shall be sealed with hot air applied sealing tape to prevent leakage and protect garment integrity. All mesh shall be covered by the WeatherTech® layer behind yokes.

The main label shall be sewn on a separate label carrier made of two plies 210T nylon lining material and the carrier shall measure 4" wide x 4 ¼" long. The carrier shall be centered and sewn into the collar and shall include size label, country of origin, and branding labels. There shall be a hanger loop of shell material centered and sewn in at the neckline of the inside of the garment. The top collar of the shell garment shall be lined with two plies of lining fabric to form a waterproof barrier.

There shall be two inside storage pockets of Nylon Tactel™ shell fabric. Each pocket shall have a 6" YKK, #3 nylon, coil, and non-separating zipper closure. Each pocket shall measure approximately 8 ½" deep by 6 ½" wide.

Mesh Lining

There shall be a mesh lining running behind the entire upper portion of the shell rain shed yoke openings to allow for maximum ventilation. The mesh shall be 100% polyester, 80G/Sq M, 150cm, Azo-free, yarn size 50 denier, knit machine 28 gauge, 9 stitches per inch, 1 mm holes, black color and shall have a two way stretch minimum 20% one way and 35% the other way. The mesh lining shall be approximately 9½" high from HPS.

Snap Ups

There shall be 16 female snaps: 6 in each front inside pocket (3 rows of 2 snaps each in each pocket that shall be reinforced with pieces of fabric. These snaps shall be hidden inside the pocket bag), and 4 snaps in lower center back. All snaps for the snap-ups shall be of a matte finish. There shall be 4 male snaps on the front waistband (2 on each side) which shall be hidden snaps, allowing for 3 levels of shortening by snap-up to the 12 female snaps on the inside pockets. There shall be 2 male snaps centered on the back elastic waistband allowing for 2 levels of shortening by snap-up to the 4 female snaps in the center back.

Front

There shall be a double storm placket over the front zipper to create a waterproof fly down the front of the jacket extending into the collar. The outside fly shall measure 27 ½" long by 2 ¾" wide. It shall be set with a ¼" single needle stitch from the top of the collar to the jacket bottom around the perimeter of the placket. The storm placket shall have sturdy interlining material for a professional appearance. There shall be a pen pocket located on the inside of the left placket measuring 1" wide by 6" long.

There shall be six hidden 24-ligne black oxidized female high compression snaps spaced to correspond with the six 24-ligne black oxidized male high compression snaps on the inner storm placket. The inner storm placket shall measure approximately 27½" long by approximately 1½" wide. It shall have interlining and be set with a ¼" single needle stitch from the top of the collar to the jacket bottom around the perimeter of the placket. The front zipper shall be a #5 two-way YKK Delrin zipper, 27½" long.

There shall be inside zippers sewn on top of the front zipper tape on both sides to accommodate optional zip-in liner/jackets (S318, S319V, S327, S525V, or S526CF). The inside zippers shall be #5 YKK Delrin reversible measuring 26" long.

There shall be two map pockets on either side of the CF zipper accessed from under the center plackets allowing for access while the CF zipper is closed. The map pockets shall be secured with 9" #3 nylon coil zipper closures. Inside each map pocket shall be a 1" wide by 6" long pen pocket.

There shall be 2 rain-shed yokes with 1½" hem across the chest, one on each side of the CF zipper. The yokes shall be fully lined with waterproof/breathable WeatherTech® nylon and faced with breathable mesh. The mesh shall extend the entire side of each yoke. The yokes shall measure approximately 10¼" in length from HPS by 10" in width to allow ventilation through the mesh lining as well as conceal optional "on demand" Hidden Agenda™ pull down flaps. There shall be a 7" #3 YKK interchangeable zipper set into the yoke on each side to attach the optional corresponding Hidden Agenda™ front panel. There shall be a 5½" deep chest pocket with 5½" zipper closure hidden under each front yoke flange. The yokes shall each close with 2 pieces of power hook fasteners and one center 18-ligne ring snap for a clean and neat appearance. Each piece of power hook shall measure approximately ¾" horizontally and 5/8" vertically and shall be placed on both sides of the hidden chest pockets located under each front yoke flange.

Back

The back shall have a rain shed yoke with a 1½" hem designed to conceal the optional Hidden Agenda™ I.D. flap system. The yoke shall be fully lined with waterproof/breathable WeatherTech® nylon and faced with breathable mesh. There shall be three power hook fastener closures measuring ¾" x 5/8" set equidistant on the yoke facing. There shall be a #3 16" YKK interchangeable zipper set into the yoke to attach the optional corresponding Hidden Agenda™ back panel. There shall be a ½" bar tack on each side of the back yoke, placed approximately 1" from the sleeve seam on each side for added stability. At the bottom inside back there shall be a 22" long #3 nylon coil covered zipper for access to the shell fabric for customization after production.

Collar

The collar shall be made of two plies of the shell material with an interlining sewn to the top collar for stability and measure 3¾" high. The collar points shall be properly shaped and symmetrical. There shall be a 7" nylon coil zipper opening on the under collar centered approximately 1" from the neckline and 2¼" from the collar top edge for the drop-in hood. The collar shall have an 8½" long x ¾" wide val cover placed over the zipper in the center of the outer collar to prevent leakage. There shall be 3½" triangle covers on both edges of the collar to secure the optional liner/jacket collars when inserted into the shell parka.

Sleeves

The sleeves shall be two-piece, semi-modified dolman construction for complete freedom of movement. There shall be a black enameled eyelet located approximately ¾" up from each cuff to allow for drainage. There shall be 9" #5 nylon coil pit zippers at the joining seams of the 2 under-sleeves located in the middle of the underarm to allow increased ventilation. The shoulder seams shall have an inside facing on the sleeve

side, 1½" wide of WeatherTech® waterproof/breathable material, and taped with sealing tape to prevent leakage.

Cuffs

There shall be a cuff formed of 2 pieces of shell material approximately 1-5/8" wide at the bottom. Half of the cuff shall be heavy-duty 1½" wide elastic stretched and sewn with 2 threads. There shall be a cuff tab adjustment approximately 1¼" wide tapering to approximately 7/8" wide by 3" long with a female high compression snap. The top half of the cuff shall be interlined and each cuff shall have three male high compression snaps for cuff adjustment. There shall be a snap tab at each inside bottom sleeve seam for snapping-in the optional liner/jacket sleeve.

Epaulets

There shall be an epaulet centered on each shoulder starting approximately ¾" from the neckline. The epaulets shall measure 7¼" long by 2" wide at the shoulder point graduating to 1-7/8" wide at the narrow end. The epaulet shall be set with a cross-stitch 1½" wide and shall have a 24 ligne enameled compression snap closure at the point. The underside of each epaulet shall have two hidden female snaps.

Mic Tabs

There shall be one mic tab under each epaulet, snapped to the shoulder seam. The mic tab shall be tapered to fit the shoulder seam and measure 2¼" wide x 4¼" long at the high point. There shall be a mic tab holder measuring 1¾" wide by 7/8" high on the front bottom of each mic tab, located ½" above the bottom edge. There shall be two male snaps 1-1/8" apart set on the top of each mic tab, 5/8" from the top edge that shall snap to the corresponding female snaps on the underside of the epaulets, and there shall be two female snaps likewise positioned on the back of each mic tab that shall snap to corresponding male snaps on the shoulder seam under the epaulets.

Pockets

There shall be two 2-way hand warmer patch front pockets with inverted pleats, measuring approximately 7 ¾" long by 7" wide with flap closures. The pocket flap shall be interlined with a non-woven material. The hand warmer pocket shall be lined with a non-pill micro fleece for warmth and comfort. The pocket flaps shall measure 3¼" long by 7-3/8" wide and shall have mitered corners.

There shall be two 24-ligne hidden female high compression snaps on the pocket flaps for closure. The pockets shall be bar tacked at both the topsides and at the hand warmer opening.

There shall be two vertical security pockets – one on each side - with an 8" x ¾" opening and set in bag with a YKK zipper closure located 1-1/8" from the storm placket and ¾" from the hand warmer pocket. The pockets shall be approximately 7" deep and shall both contain cell phone pocket inserts measuring 5" long by 3½" wide.

Badge Tab

The self-fabric badge tab shall be swift-tacked into the hand warmer pocket for optional sew on by wearer. The badge tab shall be 2¼" in length and 7/8" in width when sewn down (3¼" L x 7/8" W unfinished.) The metal eyelets shall be 1-3/8" from the center of one eyelet to the center of the other eyelet.

Bottom Band

The front bottom band shall be constructed of 2 plies of shell material, finishing 2-1/8" wide and lined with a non-woven interlining for stability and a clean appearance. There shall be two 24-ligne oxidized male compression snaps on each side, spaced approximately 1½" apart to attach the side vent closure tab when the zipper vent is worn open.

The back band shall be constructed with 1½" wide heavy-duty elastic inserted between the folded shell fabric, stretched and stitched with 2 threads. A 4" by 1-3/8" tab of 2 plies of shell material with a 24-ligne female high compression snap with a black enameled snap cap cover shall allow for closure of the bottom of the zipper vent when the vent is worn open. A corresponding 24-ligne male high compression snap shall be located on the inside back waistband to fold the tab back when not in use.

Side Vents

There shall be two side vents measuring approximately 8" long with #5 nylon coil zipper closures to allow access to guns and equipment on either side with a compression snap/tab closure (see bottom band). There shall be two black oxidized metal eyelets located above the side vents on each side to allow for water drainage.

Hood

There shall be a 3-piece hood constructed of shell material and lined with a Weather Tech® waterproof/breathable lining that shall drop in between the shell and lining at the collar. The hood shall be attached to the bottom of the zipper opening on the under collar. All hood lining joining seams shall be taped with 1" waterproof tape applied by the hot air method to prevent leakage. The hood shall have a tunneled drawcord made of multi strand braided, nylon, 1/8" wide, black in color and sewn into a channel at the perimeter of the hood with adjustment secured by a disk style #3 2-hole flat keeper lock. The keeper lock shall measure approximately 5/8" long and shall be black in color. The draw cord shall exit the hood tunnel via two 14-ligne black oxidized, metal eyelets on each side of the hood placed 1" from end of hood channel opening to center of eyelet.

Optional High Visibility Pull Down Panels

Optional high visibility pull down panels are available constructed from high performance retro-reflective material in high visibility yellow fluorescent color for both the front and rear of the jacket. The panels provide enhanced personnel conspicuity and recognition on demand and also provide a positive professional image.

Panel: The base panel is fabricated from a tough weather and solvent resistant fabric backed tape that will be sewn on to the Panel Carriers that zip on/off the jacket (see

sections on Back and Front).

Base Panel: The base panel is composed of silver cube corner (micro prism) retro-reflective elements integrally bonded to a flexible, smooth-surfaced tough and weather resistant UV stabilized polymeric film. The prism surfaces are coated with a vacuum deposition of aluminum to provide a mirror surface to the prism facets. A knit fabric backing is provided to facilitate sewing. Materials utilizing “glass-bead” or other similar retro-reflective technologies are not equivalent. The base panel is constructed of a primary base and a color layer. The silver primary base is constructed of the following layers (from top to bottom):

- Micro prism Structures
- Metalization
- PSA then Knit Fabric

Table 1: Typical Values for Silver Primary Base

Observation Angle	Entrance Angle			
	5°	20°	30°	40°
0.2°	1000	950	800	400
0.33°	400	375	325	250
1°	35	33	30	20

(All values in cd/lux/m²)

On top of the silver primary base there is a color layer. The color layer is constructed of the following layers of material (from top to bottom):

- Enhanced Surface Protection
- 6mil Fluorescent Yellow-Green Vinyl

The finished base panel is lime-green and screen processed using a custom-shade gray.

Table 1: Finished Base Panel Fluorescent yellow-green chromaticity coordinates (from ANSI/ISEA 107-2010)

	x	y
1	0.387	0.610
2	0.356	0.494
3	0.398	0.452
4	0.460	0.540

Table 2: Typical Values for Fluorescent Yellow-Green Finished Base Panel

Observation Angle	Entrance Angle			
	5°	20°	30°	40°
0.2°	800	760	640	320
0.33°	320	556	260	200
1°	28	26.4	24	16

(All values in cd/lux/m²)

Titles: The title laminated on the panel utilizes the Euro-style font, be CAD-cut for uniform consistency and is fabricated from GP430 Blue material, a tough weather and solvent resistant tape designed to be fused on to high visibility base panels. The GP430 is composed of cube corner (micro prism) retro-reflective elements integrally bonded to a flexible, smooth-surfaced tough and weather resistant UV stabilized polymeric film. The prism surfaces are coated with a vacuum deposition of aluminum to provide a mirror surface to the prism facets. Materials utilizing "glass-bead" or other similar retro-reflective technologies are not equivalent. All titles and lettering are sized per the dimensions given below. TO READ: POLICE

Panel Carrier: The front panel carriers measure approximately 7.5" wide X 4" long. The panel carrier is constructed of two layers of shell fabric in color black and sewn together with properly finished edges and a non-woven inter-lining. The panel carrier has the slide fastener side of a 7.5" #3 YKK interchangeable zipper sewn onto to top seam so that the zipper can be used to zip on to the other side of the zipper track on the jacket. The lower back corners have an approximately 1" square section of power hook - hook side, sewn approximately 1/4" from the edges of the panel. The power hook sections match corresponding power hook and loop sections on the yoke linings of the jacket. The front base panels are sewn to the front panel carriers with a stitch line going all the way around the base panel approximately 1/4" to 1/8" from the edge of the base panel. The base panel is positioned as far down on the panel carrier as practical.

The back panel carrier is constructed like the front carrier panels and measures approximately 16" long x 5" wide and uses a 16", #3 YKK interchangeable zipper. The back base panel is sewn to the back panel carrier with a stitch line going all the way around the base panel approximately 1/4" to 1/8" from the edge of the base panel. The base panel is positioned as far down on the panel carrier as practical.

Patches

Emblems will be furnished by the Agency and attached to each sleeve by the Vendor

Color

Black (003)

Sizes

Regular: S – 5XL Long: M – 5XL

SPECIFICATION FOR STYLE S318ZX
Public Safety Soft-Shell Jacket/Liner

DESIGN

The garment shall be full cut, waist length intermediate soft-shell jacket with performance features designed for public safety use. The garment shall have a full zip front to the top of the collar, side vent zippers, adjustable sleeves, wind-toggle system, two front waist draw cords, a back elastic gripper, and zippered hand warmer pockets. All dimensions and lengths are based on men's size large. Dimensions and lengths for all other sizes must be graded appropriately.

The S318ZX must be compatible to be able to zip into any of the existing Weathertech® waterproof shell jackets.

FABRIC

The fabric shall be a 3-layer soft-shell whose content is 80% polyester 20% polyurethane and whose construction is 270T/75D and weight of 315gsm. The three layers are as follows: outer face made of 100% polyester mechanical high-elastic PPT fiber, inner face made of 100% polyester 100D/144F 165-175gsm non-pill fleece, and a waterproof/breathable hydrophilic polyurethane membrane bonded in-between.

BODY DETAIL

The front zipper shall be a 26-inch YKK #5 Vislon molded zipper. There shall be an inside storm placket with a stretch bound edge and rounded at outer corners of the top and bottom ends. The hand-warmer pockets shall have a 7" long #5 nylon coil reversed teeth zipper. The hand warmer pockets shall be lined with 100% polyester soft tricot. Shoulders feature mic-tabs / epaulets permanently affixed and made from same shell fabric, placed atop a stitched triangular panel wider at the shoulder (5") and narrower at the neck seam (2¼"). The epaulets shall be 1 3/8" wide. The epaulet shall be sewn down at the armhole seam, the neck seam and the horizontal edges except for a 2 1/8" opening to accept a mic device. The opening shall be bartacked at both ends. The body of the jacket shall be tapered to allow the garment to be tucked. The sleeves shall be constructed with a separate stitched panel below the elbow. The inside of the sleeves shall be fully lined with 100% polyester smooth soft Tricot mesh, for wearer comfort, and ease of use. The gusseted cuff shall be gathered and sewn with elastic and a closure tab using power hook and loop. There shall be a loop made of shell fabric at the lower cuff sewn into the gusset seam to allow for sleeve attachment into any of the compatible Weathertech® systems shell jackets. There shall be side panels constructed under each armhole and #5 10" nylon coil side vent zippers at the bottom that shall allow access to equipment or duty belt. There shall be a 7" zippered side pocket, which aligns with the front seam of the side panel on each side of the garment. There shall be a snap tab approximately 7/8" wide by 2" long at the bottom of the side vent zipper equipped with the female snap head at the end of the tab designed to snap to the male side of the snap which shall be placed on the front bottom sweep of the jacket.

INSIDE DETAIL/POCKETS

Two large inside pockets are to be in the garment constructed of two layers of tricot with a bound opening at the top. The inside pockets shall extend from the center front to the front seam of the side panels. There shall be a tunneled draw cord at the bottom sweep on the front of the jacket. The tunnel shall be created by folding the hem of the shell fabric at the base of the garment. The draw cord shall be elasticized and the ends of the draw cord shall be sewn down inside the tunnel at the front placket vertical seam and the side seam of the front panel and shall exit the tunnel at either side of the garment through two finished eyelet holes. At the exits the draw cord shall have a bead and barrel lock to allow the cord to be tightened. There shall be a snap tab on each front panel side seam on the inside of the garment 1½” up from the bottom to secure the elasticized shock cord when tightened. The snaps on the tabs shall be compression 24L black oxidized snaps with matte finish caps. The back bottom inside band of the garment shall have a 1” wide elasticized gripper.

Patches

Emblems will be furnished by the Agency and attached to each sleeve by the Vendor

COLOR

Black (003)

CARE

Garment to be fully machine washable, cold water. Do not bleach. Tumble dry low heat, gentle cycle. Do not use fabric softener. Do not iron. Do not commercially launder and do not dry clean.

SIZES

Regular S - 5XL

Long: M - 5XL

REQUIREMENTS

All documentation listed below must be provided at the time of the bid opening.

Failure to meet any of the below requirements will result in immediate disqualification of bid.

1. Manufacturer must be ISO 9001: 2015 certified and a copy of certificate shall be included with bid and dated prior to the bid release date.

2. If bidding other than the specified garment one size each of Small/Reg; Medium/Reg; Large/Reg; XL/Reg; 2XL/Reg; 3XL/Reg; 4XL/Reg; 5XL/Reg; Medium/Long; Large/Long; XL/Long; 2XL/Long; 3XL/Long; 4XL/Long; 5XL/Long is required at the time of bid opening.

3. Manufacturer must have and submit a published lifetime warranty against product defects and component failure. No special warranties shall be accepted for this bid.

EXHIBIT D

Purchase Order Terms and Conditions

4

- A. **DELIVERY.** Delivery must be made within thirty (30) days from receipt of this purchase order unless otherwise specified. Time is of the essence and if goods are not delivered within the time specified, the Navajo Nation may reject such goods and cancel the order. Acceptance of later or defective deliveries shall not be deemed a waiver by the Navajo Nation of its right to cancel this order or to refuse to accept further deliveries. The purchase order number, account and project numbers must be shown on all packages, packing slips, invoices and correspondence relating to the order. **BACKORDERS WILL BE ALLOWED ONLY UPON AGREEMENT WITH THE PURCHASING DEPARTMENT.**
- B. **F.O.B POINT.** All prices offered herein are F.O.B. destination (on the Navajo Reservation) unless otherwise specified.
- C. **REQUIREMENT FOR WRITTEN PURCHASE ORDER.** Shipments will not be accepted and invoices will not be honored unless a valid purchase order in writing, has been issued to the vendor by the Purchasing Section of the Navajo Nation.
- D. **TERMS AND ACCEPTANCE.** This order becomes a contract (1) when a signed acknowledgment is received by the Navajo Nation, or (2) when shipment according to schedule of all or any portion of the goods covered by this order shall be made, or (3) when written approval is given vendor by the Navajo Nation of the price and delivery schedule of the goods as stated by vendor if vendor's written acknowledgment of this order contains either (a) a different price or delivery schedule or a different type of item, or (b) no price or no delivery schedule for the item or items to which the Navajo Nation's approval applies. Except as provided in the preceding sentence, a condition of this order is that any provisions printed or otherwise contained in any acknowledgment of this order, inconsistent with or in addition to the terms and conditions herein stated, and any alteration in this purchase order, shall have no force or effect, and that the vendor by such acknowledgment thereby agrees that any such provision therein or any such alteration in this order shall not constitute any part of this contract of purchase and sale. This contract contains the entire agreement of the parties, and failure of either party to enforce any of its rights hereunder shall not constitute a waiver of such rights or of any other rights hereunder.
- E. **BILLING.**
1. Submit original invoice(s) and 2 copies to the Accounts Payable Section. The Navajo Nation, P.O. Drawer 1660, Window Rock, AZ 86515. **DUPLICATE INVOICES WILL NOT BE HONORED.**
 2. Invoicing must be itemized as to items, quantities, unit prices and extended amounts.
 3. Submit a separate invoice for each purchase order. Do not combine invoicing for more than one purchase order.
 4. Invoices must be submitted immediately upon shipment.
 5. Where pricing differences or discrepancies exist between the purchase order and the invoice submitted, the purchase order will prevail. The purchaser reserves the right to accept or reject all quantities delivered not in compliance with the purchase order specifications or in excess of the quantities specified herein.
- F. **CASH DISCOUNT.** The term of any cash discount will be computed from the date of receipt and acceptance of the goods or services procured hereunder, or from the date of receipt of a correct Original invoice, whichever is later.
- G. **TAXES.** Except as may be otherwise provided in this order, the contract price includes all applicable federal, state, Indian and local taxes. In addition, the Navajo Nation claims the transaction is in any event immune from state and local sales, gross receipts, use, compensating and transaction privilege taxes under federal Indian law. Vendor expressly warrants that the contract price does include any allowance for state and local sales, gross receipts, use, compensating and transaction privilege taxes. The Navajo Nation will not reimburse or pay vendor any state and local sales, gross receipts, use, compensating and transaction privilege taxes unless the following conditions are met:
1. A governmental authority asserts a liability for such taxes against vendor has not and will not concede its liability for such taxes except as provided in Paragraph G.3(below); and
 2. The Navajo Nation at its expense is given the full opportunity to contest the liability for such taxes for and on behalf of vendor and with vendor's full cooperation; and
 3. A final determination has been made that vendor is liable for such taxes or the Navajo Nation decides it does not wish to contest vendor's liability for such taxes further.
- H. **FAIR LABOR STANDARDS ACT.** Vendor must certify that goods were produced in compliance with all applicable requirements of section 6,7 and 12 of the Fair Labor Standards Act, as amended, and of regulations and orders of the United States Department of Labor issued under section 14 thereof.
- I. **NAVAJO PREFERENCE.** If this purchase order is issued to a vendor claiming preference under the Navajo Nation Business Preference Law, then acknowledgment and/or delivery against this order shall constitute certification of current compliance, on the part of the vendor, with all applicable provisions of this Law.
- J. **CHOICE OF LAW.** The laws of the Navajo Nation will govern the interpretation, construction and enforcement of this Purchase Order, including, without limitation, the Navajo Uniform Commercial Code.
- K. **CHOICE OF FORUM.** Subject to the limits of applicable law, eg., 1. Navajo Tribe Code et seq., any dispute between the parties will be resolved in the Courts of the Navajo Nation and vendor consents to in personam jurisdiction of such courts in the event of any such dispute.
- L. **INSPECTION, WARRANTY.** Goods or services delivered (whether paid for or not) are subject to inspection, testing, and approval by the Navajo Nation before acceptance. Vendor expressly warrants that all articles, materials, services and work will conform to the applicable drawings, specifications, samples or other descriptions given in all respects. Vendor further expressly warrants that the goods or services delivered hereunder will be of good quality, material and workmanship, merchantable and free from defects. The warranty shall survive any inspection, delivery, acceptance or payment by vendor of the goods or services.
- M. **OTHER** As used herein, the titles "the Navajo Tribe" and "the Navajo Nation" are synonymous.