

Navajo Nation - Division of Community
Development – Fiscal Recovery Fund Office

Invitation for Bid No. IFB 24-05-3350GC – Rock Point Dump
Truck

Addendum No. 1: Issued June 10, 2024

This addendum forms a part of the bid and contract documents and modifies the original bid documents. Acknowledge receipt of this addendum in the bid response. Failure to do so may subject the offeror to disqualification.

ADDENDUM MODIFICATION NO. 1:

QUESTIONS:

Question No. 1: In the bid specs you have a 31 Ton electric hoist added to the truck. Will you want that as a regular hoist or are you referring to the being able to lift the bed to dump.

Answer No. 1: The 31 Ton (telescopic) Hoist was mistakenly included in the Electrical section and should have been included in the Hydraulics section of the specs. It is the cylinder hoist to raise the dump bed.

Question No. 2: The bid requested a GCVW truck and trailer 25,000 and 58,000 LBs minimum. What weight loads are you expecting to haul with the truck loaded and a trailer loaded behind the truck.

Answer No. 2: The GCWR towing requirement has been replaced with a 45,000LB GVWR requirement for the truck, and a 25,000LB GVWR tow requirement for the trailer.

See revised specifications below.

ADDENDUM MODIFICATION NO. 2:

See revised bid schedule:

Issuance of Invitation for Bids:	May 28 th , 2024
Questions on Solicitation	June 3 rd , 2024
Response to Questions (Formal Addendum):	June 7th, 2024 – June 10 th , 2024
Bids Due:	June 13th, 2024 – June 14 th , 2024, at 5:00 PM (MDT)
Bid Opening:	TBD
Notice of Selection:	TBD

REVISED Specs for Rock Point Dump Truck

	Minimum Spec	Yes	No	Exceptions
EQUIPMENT MODEL				
Truck (Freightliner M2 106 or Equivalent)				
Dumping System (Valew 15' length, 10-13 Yard Double Wall Dump Body or Equivalent)				
Color - White				
TRUCK AND CHASIS				
ENGINE				
Horsepower	300 HP			
Torque	800 FTLB			
TRANSMISSION				
Allison RDS 3500 Automatic 6 Speed	Required			
AXLES /SUSPENSION				
Gross Vehicle Weight Rating (GVWR)	45,000LBs			
Front	18,000LBs			
Rear (Tandem)	40,000 LBs			
Multi-Leaf Springs	Required			

CAB OPERATOR STATION/COMFORT				
Extended CAB	132 Inch			
Bench Seating for 3-Man work crew	Required			
Digital Instrumentation/Display	Required			
Lane Departure and Passenger Side Blind Spot Warning System	Required			
Air Conditioning	Required			
Air Driver and Passenger non-suspension bucket seats	Required			
Power Steering	Required			

Backup Alert with Rear Camera, proximity sensor	Required			
AM/FM Radio with UBS/Bluetooth	Required			
Fire Extinguisher	Required			
BRAKING SYSTEM				
Air Brakes	Required			
TOWING				
Gross Combined Weight Rating (GCWR) — Truck and 25,000 LB	58,000LBs			
28' Pintle Hitch Trailer with 25,000LB GVWR	Required			
Ph45 Pintle Hitch Assembly w/7-way electrical Outlet and Air plumbed to rear	Required			
DUMP SYSTEM				
BODY				

Length	15FT			
Capacity	10 Cubic Yard			
Floor and Cab Guard	1/4" Steel			
Sides	3/16" inner and 10ga. outer wall			
Rear Corner Post	Required			
Cheater Board Slots	Required			
Spring Loaded Tarp System	Required			
Spreader Ditch Gate	Required			
ELECTRICAL				
Hoist	31 Ton			
HYDRAULICS/PNEUMATICS				
Dump Bed Hydraulic Telescopic Hoist	31 Ton			
Telescopic Hoist / Cylinder	Required			
PTO with closed coupled Permco hydraulic pump	Required			
Hydraulic Tank	25 Gal			
Air Latch Gate	Required			
Safety locking air controls	Required			
Air plumbed to rear	Required			
OPTIONS: (Price Separately)				
3 Year On Location Preventive Maintenance/Service Agreement	Option			

3-year/3000 Hour Warranty - Powertrain, Hydraulics, Tech	Option			
5-year/5000 Hour Warranty - Powertrain, Hydraulics, Tech	Option			